

Jinghong Shower/Bath Mixers BPIR Declaration

Version: V1

Designated building product: Class 1

Declaration

Jinghong Pty Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name Jinghong Shower/Bath Mixers

Identifier Series JHD, JHX, JFH

Description

The Jinghong JHD, JHX and JFH series shower/bath mixers are available with one (without diverter) or two outlets (with diverter) & are manufactured from DZR brass complying with AS 3718. The flow rate & mixed temperature is controlled by a lift-&-turn ceramic disc cartridge with a single lever handle. They are intended for use in residential & light commercial applications, with mains pressure water supply systems. All models are available in chrome finish. Selected models are available in brushed nickel & matt black. All models have indicators which show the relative temperature range. Red for hot & blue for cold.

Scope of use

The JHD, JHX, JFH shower/bath mixers are intended for use with hot & cold water in residential & light commercial applications, with mains pressure water supply systems.

Conditions of use

Jinghong Shower/Bath Mixers must be installed by a registered plumber in accordance with the supplied instructions & in compliance with the relevant requirements of AS/NZS 3500 & AS/NZS 6400.

The water supply pipes must be flushed thoroughly to remove any debris. In-line water filters must be used.

Recommended working pressure: 100kPa to 500kPa. Maximum working pressure: 800kPa. If pressure exceeds 500kPa, a pressure limiting valve must be installed.

The maximum permitted temperature of water at the outlet is 50 degrees Celsius.

This product is cleanable and impervious to moisture — cleaning shall be done in accordance with the supplied cleaning instructions.

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.2, G12.3.5

Contributions to compliance

- | | |
|-----------------------|---|
| B2.3.1(c): | Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, Jinghong JHD, JHX, JFH Shower/Bath Mixers have a durability of at least 5 years, when installed and maintained in accordance with our supplied instructions. The Jinghong JHD, JHX, JFH Shower/Bath Mixers are designed & manufactured to AS/NZS 3718 (Water supply—Tap ware) & are Watermark certified to this standard under Licence no. WMKA20108. |
| F2.3.1: | No materials used in the construction of Jinghong Shower/Bath Mixers give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space. |
| G1.3.2: | Jinghong Shower/Bath Mixers features chrome, brushed nickel or matt black or gun metal finished surfaces for ease of cleaning. |
| G12/AS1 2.1.2: | Metallic or non-metallic water supply materials and components used in Jinghong Shower/Bath Mixers comply with AS/NZS 4020 (Testing of products for use in contact with drinking water). |

Supporting documentation

The following additional documentation supports the above statements:

Installation Instructions	Refer website.
Warranty statement(s)	Refer website.
Care & maintenance guide	Refer website.

For further information supporting Jinghong Shower/Bath Mixers claims refer to our website.

Contact details

Manufacture location	China
Manufacturer	Jinghong Approved manufacturer
Legal and trading name of importer	Jinghong Pty Ltd
Importer address for service	4F Titoki Place, Albany, Auckland, 0632
Manufacturer/importer website(s)	Jinghong.co.nz
Manufacturer/importer email	sales.jinghong@hotmail.com
Manufacturer/importer phone number	09 441 9098
Manufacturer/importer NZBN	9429036475414